



One piece dimensions shown. For two and three piece shower and tubshower bathware units allow an extra 1-1/2" to the depth of the unit for the joint assembly.



1-1/2" 38 mm



A: 25-1/4" 641 mm B: 46-1/4" 1175 mm

C: 12-1/2" 318 mm



Compliance Certifications meet or exceed the following specifications:

- CAN/ULC S102.2 M88 Flame Spread FRP laminate rating
- B45.5-11/IAPMO Z124-2011

△ LONGEVITY			
Department ACRYLIC	Reference / Job Location		
Name SIMPLICITY 9252 / DISTINCTION 9253			
Drawing by IAN MCLEAN	Scale NTS	DWG No.	
Date	Revision		

APPROVAL	
Engineering Firm	
Engineer Signature Approval	
Customer Signature of Approval	
Date	

DRAWING SUBJECT TO ENGINEERS APPROVAL

Every effort has been made to offer the most current, correct, and clearly expressed information possible. Nevertheless, inadvertent errors in information may occur. Longevity Acrylics Inc. disclaims any responsibility for errors and accuracy of the information that may be contained in its documents or web pages. Longevity Acrylics Inc. makes no warranties or representations whatsoever regarding the quality, content, completeness, suitability, adequacy, sequence, accuracy or timeliness of such information and data.