









One piece dimensions shown. For two and three piece shower and tubshower bathware units allow an extra 1-1/2" to the depth of the unit for the joint assembly.





A: 25-1/4" 679 mm B: 46" 1168 mm

C: 12-3/4" 324 mm



Compliance Certifications meet or exceed the following specifications:

- CAN/ULC S102.2 M88 Flame Spread FRP laminate rating
- B45.5-11/IAPMO Z124-2011

| △ LONGEVITY | | |
|-------------------------|--------------------------|---------|
| Department ACRYLIC | Reference / Job Location | |
| Name AL2260 / AL2263 | | |
| Drawing by IAN MCLEAN | Scale NTS | DWG No. |
| Date | Revision | |

| APPROVAL | |
|--------------------------------|--|
| Engineering Firm | |
| Engineer Signature Approval | |
| Customer Signature of Approval | |
| Date | |

DRAWING SUBJECT TO ENGINEERS APPROVAL

Every effort has been made to offer the most current, correct, and clearly expressed information possible. Nevertheless, inadvertent errors in information may occur. Longevity Acrylics Inc. disclaims any responsibility for errors and accuracy of the information that may be contained in its documents or web pages. Longevity Acrylics Inc. makes no warranties or representations whatsoever regarding the quality, content, completeness, suitability, adequacy, sequence, accuracy or timeliness of such information and data.